

MODELO	CAUDAL								
	3	6	9	12,5	15	18	20	22	
ENLACES	Hp	50	100	150	208	250	300	333	366

ALTURA DE CARGA EN METROS										
CLMX 50-32-160/1.1	1,5	21,0	20,0	18,5	16,5	15,0	12,5	10,0	8,0	
CLMX 50-32-160/1.5	2,0	26,0	24,5	22,5	20,0	18,5	15,0	12,5	9,5	
CLMX 50-32-160/2.2	3,0	30,5	29,5	27,5	26,0	24,0	22,5	20,5	18,0	
CLMX 50-32-200/3.0	4,0	40,0	37,5	35,0	33,5	31,5	30,0	26,5	25,5	
CLMX 50-32-200/4.0	5,5	51,5	50,0	48,0	45,0	43,0	41,0	39,0	30,0	

CAUDAL									
m 3/h	5	10	15	20	25	30	35	40	
l/min	83	167	250	333	417	500	583	667	

ALTURA DE CARGA EN METROS										
CLMX 65-40-125/1.5	2,0	20,0	19,0	17,5	16,0	13,0	10,5			
CLMX 65-40-125/2.2	3,0	27,0	26,0	24,0	22,0	20,0	17,0	14,0		
CLMX 65-40-125/3.0	4,0	31,0	30,0	29,0	27,0	25,0	22,0	18,0		
CLMX 65-40-160/4.0	5,5	39,0	38,0	36,5	34,0	31,0	28,0	24,0	19,0	
CLMX 65-40-200/5.5	7,5	47,0	46,0	45,0	44,0	41,0	38,0	34,0	30,0	
CLMX 65-40-200/7.5	10	52,0	51,5	51,0	50,0	48,0	45,0	42,0	38,0	
CLMX 65-40-200/11	15	69,0	69,0	68,5	68,0	68,0	66,0	64,0	60,0	

CAUDAL									
m 3/h	5	10	20	30	40	50	60	70	
l/min	83	167	333	500	667	833	1,000	1,167	

ALTURA DE CARGA EN METROS										
CLMX 65-50-125/3.0	4,0	27,0	26,0	23,0	20,0	16,0	10,0			
CLMX 65-50-125/4.0	5,5	28,0	27,0	26,0	24,0	21,0	16,0			
CLMX 65-50-160/5.5	7,5	34,5	34,5	34,0	31,5	28,5	24,0	20,0		
CLMX 65-50-200/7.5	10	41,0	41,0	40,5	39,0	36,0	32,0	27,5		
CLMX 65-50-200/9.2	12,5	52,0	52,0	51,0	49,0	45,0	41,0	37,0		
CLMX 65-50-200/11	15	57,0	56,0	55,0	53,0	51,0	48,0	42,0	30,0	
CLMX 65-50-200/15	20	69,0	68,0	67,0	65,0	64,0	62,0	57,0	50,0	
CLMX 65-50-200/18.5	25	73,0	72,0	71,0	70,0	69,0	68,0	65,0	59,0	

CAUDAL										
m 3/h	40	50	60	70	80	90	100	110	120	130
l/min	667	833	1,000	1,167	1,333	1,500	1,667	1,833	2,000	2,167

ALTURA DE CARGA EN METROS										
CLMX80-65-125/4.0	5,5	19	18	17	15	13	11	9		
CLMX80-65-125/5.5	7,5	22	21	20	19	18	17	15	13	10
CLMX80-65-125/7.5	10,0	27	26	25	24	23	22	20	18	15
CLMX80-65-125/9.2	12,5	30	29	29	28	27	26	25	23	22
CLMX80-65-160/11	15,0	36	35	34	33	32	31	29	27	25
CLMX80-65-160/15	20,0	44	43	42	40	39	38	37	36	34
CLMX80-65-200/18.5	25,0	53	52	51	50	49	48	47	45	44
CLMX80-65-200/22	30,0	60	59	58	57	56	55	54	53	51
CLMX80-65-200/30	40,0	72	72	71	70	69	68	67	66	65

m 3/h	60	80	100	120	140	160	180	192	200
l/min	1,000	1,333	1,667	2,000	2,333	2,667	3,000	3,200	3,333

ALTURA DE CARGA EN METROS										
CLMX100-80-160/11	15,0	26	25	23	22	20	17	14	11	
CLMX100-80-160/15	20,0	35	33	31	29	27	24	21	20	18
CLMX100-80-160/18,5	25,0	38	37	36	35	33	30	27	25	22
CLMX100-80-200/22	30,0	46	44	42	40	38	35	31	29	26
CLMX100-80-200/30	40,0	57	56	55	53	50	47	44	42	39
CLMX100-80-200/37	50,0	66	65	63	61	59	56	53	51	48

